



Evaluation of Microbial Quality of *Fufu* Samples Prepared Using Conventional and Mechanical Methods in Kumasi Metropolis

Francis Xavier Tebri ^a, Doreen Dedo Adi ^{a*},
Yaa Mawufemor Akubia ^a and Abena Sekyere ^a

^a Department of Hospitality and Tourism Education, Akenten Appiah-Menka University of Skills Training and Entrepreneurial Development, Kumasi, Ghana.

Authors' contributions

This work was carried out in collaboration among all authors. Author FXT did the conceptualization, methodology, data analysis, manuscript writing. Author DDA did the supervision, methodology, data analysis, manuscript writing, editing. Authors YMA and AS did the methodology, data analysis and editing. All authors read and approved the final manuscript.

Article Information

DOI: <https://doi.org/10.9734/ejnf/2024/v16i71450>

Open Peer Review History:

This journal follows the Advanced Open Peer Review policy. Identity of the Reviewers, Editor(s) and additional Reviewers, peer review comments, different versions of the manuscript, comments of the editors, etc are available here: <https://www.sdiarticle5.com/review-history/117606>

Original Research Article

Received: 03/05/2024

Accepted: 26/05/2024

Published: 31/05/2024

ABSTRACT

Aim: The study aimed at evaluating the microbial quality of conventionally (CV) and mechanically (MC) prepared *fufu* samples in the Kumasi Metropolis of Ghana.

Study Design: The study used 2 x 5 x 2 experimental design constituting two *fufu* preparation methods (CV and MC), five different vending locations, and two sample types (*fufu* samples and water samples) from each vendor.

Materials and Methods: A total of ten (10) *fufu* and water samples each were conveniently collected and analysed using standard microbiological procedures.

*Corresponding author: Email: ddadi@amusted.edu.gh;

Cite as: Tebri, F. X., Adi, D. D., Akubia, Y. M., & Sekyere, A. (2024). Evaluation of Microbial Quality of *Fufu* Samples Prepared Using Conventional and Mechanical Methods in Kumasi Metropolis. *European Journal of Nutrition & Food Safety*, 16(7), 1–8. <https://doi.org/10.9734/ejnf/2024/v16i71450>

Place and Duration of Study: The study was carried out in the Kumasi Metropolis of Ghana, in March 2022.

Results: The total aerobic count in the conventional and mechanical prepared samples ranged from 5.2×10^7 cfu/g to 4.5×10^8 cfu/g and 5.4×10^7 cfu/g to 1.35×10^8 cfu/g respectively. The total aerobic count in the water samples ranged between 9.7×10^6 cfu/ml and 1.35×10^9 cfu/ml in (CV) and 1.53×10^6 cfu/ml – 6.3×10^8 cfu/ml in (MC). Both the *fufu* and water samples from the vendors had unsatisfactory levels of total and faecal coliform count, *Staphylococcus aureus* count, and yeast count irrespective of the processing method (CV and MC).

Conclusion: The *fufu* processing methods did not influence its microbial qualities positively. Hence Good Hygienic Practices are essential to ensure its microbiological safety.

Keywords: microbial quality; *fufu*; Kumasi; cassava; food safety; cassava.

1. INTRODUCTION

Fufu is a staple dish in western and central Africa that is thought to have generated from Akan people in Ghana [1]. The majority of Ghanaians eat *fufu* as a staple food especially the Akans. *Fufu* is traditionally made by boiling unripe mature plantains, cassava, cocoyams or yams until they are tender [2,3]. The cooked tubers or plantains are crushed with a pestle and mortar, turning them repeatedly with wet hands until the mixture forms a dough [2,4,5,6]. Ordinarily, one person stands and manually uses the pestle to pound the cooked ingredients in the mortar in rhythmic strokes, while the other person turns the ingredients in the mortar, with wet hands and intermittently adds water to form the *fufu* dough [7,1]. This is a time-consuming and difficult operation, particularly if it needs to be prepared commercially or in large quantities. This resulted in the creation of the automated *fufu* processing method (using *fufu* machine), which requires less labour than the conventional approach [8]. The components of the *fufu* machine include the electric motor, shaft, trough, pulleys, propellers, and a frame with vents to allow for proper cooling of the machine while it is in use. The *fufu* milling machine receives the cooked roots or tubers through an automated process. The *fufu* is subsequently mechanically processed by the mill and extruded as a dough. The extruded dough is briefly pounded and formed into balls for eating [2]. The prepared *fufu* is typically served with the soup of choice. The safety and quality of *fufu* is largely dependent on the hygienic practices of the producers. It is particularly perishable because it is often offered in the wet form (moisture content of roughly 50%) [9]. Studies on the microbiological quality of different street foods have been conducted in Ghana. The hygiene practices during preparation and the microbial quality of the water used to moisten hands when processing *fufu* can be a source of

contamination [10]. These could inevitably lead to modifications in the food product's texture, taste, look, and fragrance, as well as a decline in its acceptability and safety [9]. Mechanized *fufu* processing has become common in Ghana's cities, and most people choose to use it instead of the more antiquated pestle and mortar approach [1,11]. A comparative approach to evaluate whether the mechanized processing of *fufu* will improve microbial load is therefore very essential. This study therefore aimed at the evaluation of the microbial quality of *Fufu* samples prepared from conventional and mechanical methods in Kumasi metropolis.

2. MATERIALS AND METHODS

2.1 Study Area

The study was carried out in the Kumasi Metropolis (Kejetia) of the Ashanti region of Ghana, West Africa

2.2 Sampling and Preparation

Samples of *fufu* and water used during processing were obtained from ten different *fufu* sellers (5 conventional and 5 mechanical) within the Kumasi Metropolis (Kejetia) of the Ashanti region. The *fufu* samples were collected into sterile Zip-lock bags using a sterile spatula which was sterilized with 70% ethanol prior to sampling. The water samples were collected into sterile sampling bottles, sealed and labelled accordingly. The *fufu* and water samples were transported with ice to the Microbial Biotechnology laboratory of the Department of Biochemistry, KNUST.

2.3 Microbial Analysis

Serial dilution: For all the samples, 5 grams were added to 45 ml sterile

peptone water and homogenized in a stomacher (Lad Blender, Model 4001, Seward Medical, England), for 30 s at normal speed. One millilitre aliquot of each dilution, prepared using suitable ten-fold dilutions, was directly inoculated into sterile Petri dish containing Mannitol Salt Agar, MacConkey agar, Plate Count agar and Potato Dextrose Agar and spread.

2.4 Enumeration of Total Aerobic Count (TAC), Total Coliform Count (TCC), *Staphylococcus aureus*, Yeast and Mould Count

All the enumeration were done by spread plate technique. Aerobic bacteria were enumerated on Plate Count Agar (PCA) (Oxoid CM325; Oxoid Ltd., Basingstoke, Hampshire, UK). The plates were incubated at 37 °C for 48 hours. Total coliforms and *E. coli* were determined on MacConkey agar. The plates were incubated at 37 °C for 48 hours. *Staphylococcus aureus* was determined on Mannitol Salt Agar (Oxoid Ltd, Hampshire, England). The plates were incubated at 37 °C for 24 hours. Yeasts and moulds were enumerated on a fresh potato dextrose agar plate. The plates were incubated at 25 °C for a week.

2.5 Characterization and Identification of Bacteria Isolates from *Fufu*

The bacteria were isolated and identified using standard microbiological methods such as the catalase test, potassium hydroxide test, and Gram stain.

2.6 Statistical Analysis

Data was analysed using SPSS version 23. Analysis of variance (ANOVA) was used to determine differences in the microbial qualities of the samples and the Duncan's multiple range test was used to compare means at 5% significant level.

3. RESULTS

3.1 Microbial Quality and Safety of *Fufu* Samples

Total aerobic bacteria contamination of *Fufu* samples: The amount of total aerobic bacteria in conventional and mechanical samples ranged from 5.2×10^7 cfu/g to 4.5×10^8 cfu/g and $5.$

4×10^7 cfu/g to 1.35×10^8 cfu/g respectively (Table 1). Similar study by Adegbehingbe [9] also reported a total bacterial count of (3.43×10^6 to 5.3×10^6 cfu/g) in *fufu* samples which exceeded the acceptable limit of 1.0×10^5 cfu/g for ready to eat food [12,13]. There was no significant difference ($P=0.05$) in the bacterial load of both conventional and mechanically processed food. This study indicates that the bacterial load of both conventional and mechanically processed *fufu* were above the required standards. Annan et al. (2018) also reported an unsatisfactory bacterial load of (6.8×10^5 - 2.2×10^6) in conventionally processed *fufu* and a borderline bacterial load of (3.4×10^3 - 4.3×10^4 cfu/g) for mechanically processed *fufu*. The processing technique, the quality of the water utilized in the production process, and the duration of exposure during sale could all be contributing factors to the discrepancy in the microbial count between these investigations. The findings of the study indicated high levels of mesophilic bacterial contamination in the water samples used by both conventional and mechanical *fufu* service providers. The detected levels of contamination (9.7×10^6 cfu/ml – 1.35×10^9 cfu/ml and 1.53×10^6 cfu/ml – 6.3×10^8 cfu/ml) for the respective conventional and mechanical processing methods exceed the safe and acceptable limits for mesophilic bacteria (5.0×10^2 cfu/ml) in portable water. This confirms that the quality of water used during the preparation of *fufu* was a source of contamination. There was no statistically significant difference ($P=0.05$) in the bacterial load of water used for both conventional and mechanically processed *fufu*, although the bacterial load in the water used by the conventional method was higher than that of the mechanical process (Table 1).

3.2 Total Coliform Counts

The total coliform counts of the *fufu* samples ranged from 6.1×10^6 cfu/g to 3.7×10^7 cfu/g for conventionally produced *fufu* and from 6.5×10^6 cfu/g to 5.6×10^7 cfu/g for mechanically produced *fufu* (Table 2). The total coliform counts of the *fufu* samples were higher than the required amount of 1.0×10^2 cfu/g [12]. There was a statistically significant difference between total coliform counts of the *fufu* samples produced conventionally and those produced mechanically ($P=0.05$). This results was similar to work done by Annan et al. [2], who reported the total coliform count of 1.4×10^3 - 3.1×10^4 cfu/g and 9.7×10^1 - 4.1×10^2 cfu/g for conventionally and mechanically produced *fufu* respectively also

above the acceptable limit. Akoma [14] also reported the presence of *Klebsiella* sp. and *Pseudomonas* sp. in *fufu* samples. The presence of coliforms in food is used as a hygiene indicator; thus their presence is an indication of poor hygiene practices during food preparation [15]. This indicates that all the *fufu* samples collected during the study are hazardous and unsanitary for human consumption. The detected coliform

contamination levels were 5.3×10^6 cfu/ml – 1.28×10^8 cfu/ml for the water samples from conventional *fufu* and 6.9×10^6 cfu/ml – 3.5×10^7 cfu/ml for the water used for mechanical *fufu* production. Although the coliform load in the water samples used for the *fufu* samples prepared by the mechanical methods were lower than that of the conventional, there were no statistically significant difference between them ($P=0.05$).

Table 1. Total aerobic count of *fufu* and water samples from conventional and mechanical processing methods

Vendors	<i>Fufu</i> samples(cfu/g)		Water Samples(cfu/g)	
	Conventional	Mechanical	Conventional	Mechanical
1	$9.4 \times 10^7 \pm 0.8^a$	$1.3 \times 10^8 \pm 0.1^d$	$1.0 \times 10^9 \pm 0.2^c$	$1.5 \times 10^6 \pm 0.3^a$
2	$5.2 \times 10^7 \pm 0.3^a$	$1.1 \times 10^8 \pm 0.3^c$	$9.4 \times 10^7 \pm 0.5^{ab}$	$7.0 \times 10^7 \pm 0.2^b$
3	$8.2 \times 10^7 \pm 0.1^a$	$7.8 \times 10^7 \pm 0.2^b$	$1.3 \times 10^8 \pm 0.1^b$	$6.3 \times 10^8 \pm 0.5^c$
4	$4.5 \times 10^8 \pm 0.3^c$	$6.3 \times 10^7 \pm 0.1^a$	$4.3 \times 10^7 \pm 0.2^a$	$9.3 \times 10^7 \pm 0.1^b$
5	$3.7 \times 10^8 \pm 0.4^b$	$5.4 \times 10^7 \pm 0.3^a$	$5.2 \times 10^7 \pm 0.4^a$	$1.1 \times 10^7 \pm 0.2^a$

Data expressed as mean \pm SD

Means bearing different superscripts in the same column are significantly different ($P=0.05$)

Table 2. Total Coliform counts of *fufu* and water samples from conventional and mechanical processing methods

Vendors	<i>Fufu</i> samples (cfu/g)		Water Samples(cfu/g)	
	Conventional	Mechanical	Conventional	Mechanical
1	$9.5 \times 10^5 \pm 0.1^a$	$3.5 \times 10^7 \pm 0.6^a$	$5.3 \times 10^6 \pm 0.3^a$	$6.9 \times 10^6 \pm 0.5^a$
2	$6.3 \times 10^6 \pm 0.4^a$	$5.6 \times 10^7 \pm 0.2^b$	$1.2 \times 10^8 \pm 0.2^b$	$3.6 \times 10^7 \pm 0.3^d$
3	$3.7 \times 10^7 \pm 0.5^b$	$4.7 \times 10^7 \pm 0.4^c$	$4.5 \times 10^7 \pm 0.5^c$	$1.0 \times 10^7 \pm 0.2^{bc}$
4	$8.4 \times 10^6 \pm 0.2^a$	$6.5 \times 10^7 \pm 0.3^d$	$3.9 \times 10^7 \pm 0.3^c$	$1.1 \times 10^7 \pm 0.1^c$
5	$6.0 \times 10^6 \pm 0.4^a$	$6.6 \times 10^6 \pm 0.1^e$	$1.2 \times 10^7 \pm 0.4^d$	$8.7 \times 10^6 \pm 0.3^{ab}$

Data expressed as mean \pm SD

Means bearing different superscripts in the same column are significantly different ($P=0.05$)

Table 3. Faecal Coliforms (*Escherichia coli*) counts in *fufu* and water samples from conventional and mechanical processing methods

Vendors	<i>Fufu</i> samples (cfu/g)		Water Samples (cfu/g)	
	Conventional	Mechanical	Conventional	Mechanical
1	$4.4 \times 10^5 \pm 0.5^a$	0.0	$4.4 \times 10^5 \pm 0.6^a$	0.0
2	$5.8 \times 10^6 \pm 0.3^b$	0.0	$8.4 \times 10^6 \pm 0.5^b$	$6.8 \times 10^6 \pm 0.4^b$
3	$5.3 \times 10^6 \pm 0.2^b$	$9.4 \times 10^4 \pm 0.2^a$	0.0	0.0
4	$4.5 \times 10^4 \pm 0.6^a$	$4.7 \times 10^6 \pm 0.4^b$	0.0	$7.6 \times 10^6 \pm 0.2^c$
5	$2.0 \times 10^5 \pm 0.5^a$	$4.4 \times 10^6 \pm 0.5^b$	$4.1 \times 10^5 \pm 0.4^a$	$6.3 \times 10^4 \pm 0.3^a$

Data expressed as mean \pm SD

Means bearing different superscripts in the same column are significantly different ($P=0.05$)

Table 4. Levels of *Staphylococcus aureus fufu* and water samples

Vendors	<i>Fufu</i> samples (cfu/g)		Water Samples (cfu/g)	
	Conventional	Mechanical	Conventional	Mechanical
1	3.2x 10 ⁵ ±0.4 ^{ab}	1.1x 10 ⁵ ±0.1 ^c	9.3x 10 ⁴ ±0.2 ^b	3.5x 10 ⁴ ±0.5 ^{ab}
2	5.7x 10 ⁴ ±0.2 ^a	5.9x 10 ⁵ ±0.3 ^d	3.2x 10 ⁴ ±0.5 ^a	6.9x 10 ⁴ ±0.2 ^b
3	1.1x 10 ⁵ ±0.3 ^a	1.2x 10 ⁵ ±0.2 ^c	3.2x 10 ⁵ ±0.1 ^c	3.4x 10 ³ ±0.3 ^a
4	5.5x 10 ⁶ ±0.2 ^c	7.0x 10 ⁴ ±0.1 ^b	3.3x 10 ⁴ ±0.2 ^a	4.1x 10 ⁵ ±0.1 ^c
5	4.6x 10 ⁵ ±0.3 ^b	9.5x 10 ³ ±0.3 ^a	3.8x 10 ³ ±0.4 ^a	6.3x 10 ⁴ ±0.2 ^b

Data expressed as mean ±SD

Means bearing different superscripts in the same column are significantly different (P=.05)

Table 5. Contamination levels of yeast in *fufu* and water from conventional and mechanized processing

Vendors	<i>Fufu</i> samples (cfu/g)		Water Samples (cfu/g)	
	Conventional	Mechanical	Conventional	Mechanical
1	1.0x 10 ⁶ ±0.5 ^a	5.8x 10 ⁶ ±0.1 ^d	3.4x 10 ⁷ ±0.3 ^b	9.4x 10 ¹ ±0.3 ^a
2	1.1x 10 ⁶ ±0.2 ^a	4.5x 10 ⁴ ±0.3 ^a	4.6x 10 ⁷ ±0.5 ^c	3.6x 10 ⁵ ±0.2 ^b
3	4.4x 10 ⁶ ±0.1 ^b	1.3x 10 ³ ±0.2 ^a	3.9x 10 ⁷ ±0.1 ^{bc}	5.3x 10 ⁵ ±0.5 ^b
4	8.3x 10 ⁶ ±0.3 ^c	9.5x 10 ⁵ ±0.1 ^b	1.1x 10 ⁷ ±0.2 ^a	6.5x 10 ⁶ ±0.1 ^c
5	8.1x 10 ⁵ ±0.3 ^a	4.8x 10 ⁶ ±0.3 ^c	8.4x 10 ⁶ ±0.4 ^a	1.1x 10 ⁶ ±0.3 ^d

Data expressed as mean ±SD

Means bearing different superscripts in the same column are significantly different (P=.05)

Table 6. Contamination levels of mould in *fufu* and water from conventional and mechanized processing

Vendors	<i>Fufu</i> samples (cfu/g)		Water Samples (cfu/g)	
	Conventional	Mechanical	Conventional	Mechanical
1	0.0	0.0	0.0	9.3x 10 ¹ ±0.3 ^a
2	0.0	0.0	2.8x 10 ¹ ±0.3 ^c	3.1x 10 ¹ ±0.2 ^b
3	0.0	0.0	0.0	3.5x 10 ² ±0.5 ^c
4	0.0	0.0	2.3x 10 ¹ ±0.2 ^a	4.7x 10 ² ±0.1 ^d
5	0.0	7.0x 10 ¹ ±0.2	6.0x 10 ¹ ±0.3 ^b	1.5x 10 ² ±0.3 ^e

Data expressed as mean ±SD

Means bearing different superscripts in the same column are significantly different (P=.05)

3.3 Faecal Coliform (*Escherichia coli*) Contamination of *Fufu*

The faecal coliform (*Escherichia coli*) in the conventionally pounded *fufu* (4.5x10⁴ to 5.8x10⁶ cfu/g) were higher than that of the mechanically milled *fufu* (9.4x10⁴ to 4.7x10⁶ cfu/g). There was no statistically significant difference between the faecal coliform of both conventionally processed *fufu* and mechanically processed ones (P=.05). The findings of this study was similar to the work done by Annan et al. [2], who also reported similar trends. The detected levels of faecal coliforms in the *fufu* samples from both conventional and mechanical processed *fufu* were significantly high and exceeded the safe and acceptable limit of 20 - <100cfu/g [13]. The findings of the study also indicated the presence of some faecal coliforms in the water used by both methods (conventional; 4.1x10⁵cfu/g –

8.4x10⁶ cfu/g and mechanical 6.3x10⁴ cfu/g and 7.5x10⁶ cfu/g). However, some *fufu* milling machine operators recorded no faecal coliform contamination in both *fufu* and water samples which is indicative of relatively better hygienic conditions and relatively good water quality at those facilities (Table 3).

3.4 Contamination of *Fufu* and Water by *Salmonella typhi*

The results of the *Salmonella* test in this study showed that there were no *Salmonella* bacteria found in any of the *fufu* and water samples. This research shows that the machines, tools, and water used in making *fufu* are free from *Salmonella* bacteria; hence *fufu* consumers in the metropolis may not face treat of salmonellosis and typhoid from it consumption.

3.5 Contamination Levels of *Staphylococcus aureus* in *fufu* and Water

Conventionally processed *fufu* recorded *Staphylococcus aureus* count ranging from 5.7×10^4 - 5.5×10^5 cfu/g and mechanically processed *fufu* recorded *Staphylococcus aureus* count from 9.5×10^3 - 5.9×10^5 cfu/g. There was no statistically significant difference in the *Staphylococcus aureus* count between the conventionally and mechanically processed *fufu* ($P=0.05$). This differs from the study carried out by Annan et al. [2] who describe the *S. aureus* count of traditionally processed *fufu* (1.5×10^2 - 2.0×10^3 cfu/g) and mechanically processed ones (0 - 8.9×10^2 cfu/g) as borderline ($20 \leq 10^4$). Another study by Akoma [14] and Ewanfo [16] reported the presence of *Staphylococcus aureus* in *fufu* samples in Lokoja and Benin market respectively. Food poisoning can occur when a food handler contaminates food, or from surfaces and equipment that the food comes into contact with. *Staphylococcus aureus* is a common bacteria that can be found on the skin, hair, noses, and throats of people and animals [2]. Furthermore, the storage conditions of the *fufu* samples favors the rapid growth of the *Staphylococcus aureus* to levels ($>10^5$ cfu/g) which initiates toxin production [17]. *Staphylococcus aureus* in both conventional and mechanical *fufu* samples are classified as unsatisfactory ($>10^4$ cfu/g), however, *fufu* that was conventionally processed had a higher microbiological load than *fufu* that was made using the mechanical method. The amount of *Staphylococcus aureus* in water used for conventional and mechanical processing ranged from 3.8×10^3 cfu/g to 3.2×10^5 cfu/g and 3.4×10^3 cfu/g to 6.4×10^4 cfu/g respectively. *Staphylococcus aureus* in the water used for conventional processed *fufu* are classified as unsatisfactory ($>10^4$ cfu/g) whereas the *Staphylococcus aureus* count in mechanically processed *fufu* are classified as borderline ($20 \leq 10^4$ cfu/g) [13]. There was no statistically significant difference in the *Staphylococcus aureus* count of water used for conventionally and mechanically processed *fufu*. ($P=0.05$).

3.6 Contamination Levels of Yeast and Moulds in *fufu* and Water

The recorded yeast counts exceeded the acceptable limit of 1.0×10^3 cfu/g in both *fufu* (Conventional: 8.1×10^5 cfu/g - 8.3×10^6 cfu/g, mechanical 1.3×10^3 cfu/g - 5.8×10^6 cfu/g) and

water samples (Conventional: 8.5×10^6 cfu/g - 4.6×10^7 cfu/g, mechanical 9.4×10^2 cfu/g - 6.5×10^6 cfu/g) obtained from the vendors using both conventional pounding and mechanized milling (Tables 5 and 6). There was no statistically significant difference in the yeast count of the *fufu* from the traditional and mechanized methods ($P=0.05$) however, there was a statistically significant difference in the yeast count of the water from the traditional and mechanized methods ($P=0.05$). The outcome of the assay indicated only 1(10%) of the *fufu* samples recorded mould colonization with mean count of 7.0×10^1 cfu/g which came from a sample from the mechanized mills. There was no statistically significant difference in the mould count of the *fufu* from the traditional and machine methods, however, there was a statistically significant difference in the mould count of the water from the traditional and machine methods. The amount of moulds found in the *fufu* and water used for processing was lower than the safe limit of 1.0×10^3 cfu/g. The ability of moulds to generate spores makes them ubiquitous environmental pollutants. Their appearance in the *fufu* samples utilized in this investigation may have been due to this [9,18].

4. CONCLUSION

This research has demonstrated that *fufu* prepared by both conventional and mechanized process within Kumasi metropolis contain high microbial load which exceeds safe and acceptable standards and are unsafe and unwholesome for human consumption. *Escherichia coli*, and *Staphylococcus aureus* were detected in the *fufu* samples. It is worthy to note that most vendors serve *fufu* with hot soup which has the potential of lowering the microbial load of the *fufu*, however if the soup used is cold, it can contribute to microbial load which will be detrimental to the health of consumers. The water used in the preparation of the *fufu* also failed the microbial tests and were classified as unsafe with total aerobic and coliform counts exceeding the acceptable limits. The water samples were also contaminated with *Escherichia coli* and *Staphylococcus aureus* with counts exceeding the safe and acceptable limit. Although both the conventional and mechanized processing had high microbial load, the microbial count in the mechanized processing were lower than the conventional processing method. As a result, when processing *fufu*, appropriate hygienic conditions and good preparation practices are required.

COMPETING INTERESTS

Authors have declared that no competing interests exist.

REFERENCES

1. Suglo P, Kpordze WS, Saba CK. Multidrug resistant *Salmonella* species isolated from fufu grinding machines in Ghana. *African Journal of Food, Agriculture, Nutrition and Development*. 2022;22(3):19965-19978.
2. Annan T, Andoh-Odoom AH, Atter A, Ampah J, Ofori H. Technical report on the comparison of the effect of two types of fufu processing methods on its microbial quality. Council for Scientific and Industrial Research (CSIR), Food Research Institute, Ghana; 2019.
3. Otoo GS, Essuman EK, Gyimah V, Bigson K. Quality attributes of fufu: Instrumental and sensory measurement. *Sci Afr*. 2018;1:e00005.
4. Agbor EA, Tiku BP, Hermann MD. Effect of microbial inoculant on physicochemical and microbiological properties of cassava fermentation process and fufu produced. *Asian Food Science Journal*. 2022;21(3):1–9. Available:<https://doi.org/10.9734/afsj/2022/v21i330411>
5. Agbor AE, Ariahu CC, Adie PA, Ariahu E. Quality evaluation of fermented pre gelatinized unripe plantain and soybean based complementary foods 1: Physicochemical, sensory and rheological properties. *European Journal of Nutrition & Food Safety*. 2024;16(5):66–79. Available:<https://doi.org/10.9734/ejnfs/2024/v16i51423>
6. Odom TC, Udensi EA, Nwanekezi EC. Microbiological qualities of hawked retted cassava fufu in Aba metropolis of Abia state. *Nigerian Food Journal*. 2012 Jan 1;30(1):53-8.
7. Addo MG, Mutala AH, Badu K. Comparison of microbiological and sensory qualities of 'fufu' processed from grinding machines and the traditional method at Ayigya in the Kumasi Metropolis, Ghana. *Microbiology Research Journal International*. 2020;30(5):20-26.
8. Pouza JC, Opoku F, Aboagye B. Development and testing of a motorized cassava fufu pounding machine. *International Journal of Engineering Technology (UAE)*. 2016;5(1):1-6.
9. Adegbehingbe KT, Adeleke BS, Bello MO, Adejoro DO, Ojo OR, Fasanmi TT. Microbiological assessment of fufu produced from Akoko area of Ondo State. *International Journal of Research and Scientific Innovation*2019; 6(6):85-91.
10. Ofosu AH, Dzigbede BA, Agidi JEL, Adjei J, Koranteng A. A study into microbial quality of ready to eat foods sold in the Sunyani Municipality of Ghana. *Global Journal Biology Agriculture Health & Sciences*. 2014;3(3):84-91.
11. Nkansah MA, Agorsor PI, Opoku F. Heavy metal contamination and health risk assessment of mechanically milled delicacy called fufu. *International Journal of Food Contamination*. 2021;8(1):6.
12. Ghana Standards Authority. (GS:955). Guidelines for Assessing the Microbiological Safety of Ready-to-Eat Foods in Ghana; 2019.
13. Jovanovic J, Ornelis VF, Madder A, Rajkovic A. *Bacillus cereus* food intoxication and toxicoinfection. *Comprehensive Reviews in Food Science and Food Safety*. 2021;20(4):3719-3761.
14. Akoma ON, Ononugbo CM, Eze CC, Chukwudozie KI, Ogwu JE. Microbial assessment of selected, locally-fermented and ready-to-eat cassava products sold in Ilokoja, Nigeria. *Asian Food Sci. J*. 2019;8:1-9.
15. Castro-Ibáñez I, López-Gálvez F, Gil MI, Allende A. Identification of sampling points suitable for the detection of microbial contamination in fresh-cut processing lines. *Food Control*. 2016;59: 841-848.
16. Health Protection Agency. Guidelines for assessing the microbiological safety of ready-to-eat foods. London: Health Protection Agency; 2009.
17. Ewanfo IJ, James IM, Ugueri U. Microbiological quality of commercially ready-to-eat fufu sold in Benin City, Nigeria. *American Journal of Food*. 2017;2(5):26-30.

18. Rajkovic A, Jovanovic J, Monteiro S, Decler M, Andjelkovic M, Foubert A, Uyttendaele M. Detection of toxins involved in foodborne diseases caused by Gram-positive bacteria. *Comprehensive reviews in food science and food safety*. 2020;19(4):1605-1657.

© Copyright (2024): Author(s). The licensee is the journal publisher. This is an Open Access article distributed under the terms of the Creative Commons Attribution License (<http://creativecommons.org/licenses/by/4.0>), which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

Peer-review history:

The peer review history for this paper can be accessed here:

<https://www.sdiarticle5.com/review-history/117606>